SAB-DR SERIES

Features

- The New SAB series represents a new standard level for analytical balances. They feature a new, readable LCD display a clearer presentation of the weighing result.
- Besides, the display has a new text information line allowing to show additional messages and data, e.g. product name or tare value.
- Automatic internal adjustment, which takes into consideration temperature changes and time flow.
- Several communication interfaces: 2 x RS 232, type A USB, type B USB and optional WiFi.
- The Informrmation system is based on 5 databases:
 - up to 10 users,
 - up to 1000 products,
 - up to 1000 weighments,
 - up to 10 tares,
 - ALIBI memory up to 100 000 weighments.



SEMI-MICRO ANALYTICAL BALANCE



MODEL	CAPACITY (gm)	RESOLUTION (mg)	PAN (mm)	REPEATABILITY (mg)	LINEARITY (mg)	RESPONSE TIME (Sec.)
Auto Internal Calibration						
SAB 265DR	60 / 220	0.01/0.1	⊗ 80	<u>+</u> 0.03/0.1	<u>+</u> 0.07/0.2	5~8
SAB 285DR	80 / 220	0.01/.0.1	⊗ 80	<u>+</u> 0.05/0.1	<u>+</u> 0.07/0.2	5~8
SAB 205DR	100/220	0.01/0.1	⊗ 80	<u>+</u> 0.08/0.1	<u>+</u> 0.07/0.2	5~8
SAB 414S	410	0.1	⊗ 80	<u>+</u> 0.2	<u>+</u> 0.4	5~8

* Repeatability is expressed as a standard deviation from 10 weighing cycles.

* Non-condensing conditions.

Optional Accessories

Density Kit • Data Printer • Software • Test Weights



3/10-11, Dev Industrial Esate, B/H Gorwa BIDC, Nr. Water Tank, Gorwa, Vadodara 390016, India. Tel: +91-265-2291527 Fax: +91-265-2311 842 Email: sales@scale-tec.in Url: www.scale-tec.in



