Weighing Indicator

SCALE-TEC
MEASUREMENT WITH CONFIDENCE



Weighing Indicator–ABS Body

The weighing indicator is suitable to work with electronic floor scales, electronic truck scales, rail scales and other static weighing systems.

- Operating voltage: AC220V or DC15V;
- 6-digit 0.8-inch LED brightness adjustable display;
- The optional RS232 serial port can be connected to computer for communication or external display.
- Options for stainless steel and plastic sprayed housing.
- Linearity Calibration with fixed3steps
- Smart Load Cell Cornering;1. Individual Cornering, 2. Shaft Cornering, 3. Manual Cornering
- Auto Zero, Speed Control, Multiple Unit
- Remote Display Port is Provided to Connect Optional½inch, 1 inch, 2.3 inch OR 4Inch bright LED Display

Display	
Mode of display	6-digit bright LED 6 characters of status indication
Clock	Optional
Interface	
Serial port	Optional RS232, can be connected to the host computer and download the software program for digital sensor upgrading.
Operating Environment	
Power supply	
Operating Temperature	AC: AC220V±10%; 50~60HZ; DC: DC15V±10% (can be connected to battery)
Storage and Transportation Temperature	-10°C~40°C
Relative Humidity	-25°C~55°C
Protection Level	<85%RH

SCELTEC MECHATRONIC PVT. LTD.
T: +91 99099 66404
info@scale-tec.in
www.scale-tec.in